



## YA lever hoist

### Produkt information



Model Rema® YA lever hoist is a robust lever hoist suitable for lifting, pulling, spanning and clamping in any directions.

#### Properties

- Grade 10 Galvanized load chain with high tensile strength (EN 818/7).
- Compact construction and very low self-weight.
- Reliable self-locked brake which will retain the load at every required height.
- Hooks provided with safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Patented guide for the load chain.
- A double spring on each catch for additional safety.

#### Standard delivery

- 1,5 m lifting height (max distance between top and bottom hookpositions).

#### Option

- Available in other lifting heights.

**Mærkning:** I henhold til standard, CE

**Standard:** EN 818-7, EN 13157

Art. nr.	GTIN No.	WLL ton	Løftehøjde m	Model	Lastkæde diameter x pitch mm	Maks. håndstyrke på krumtap kg	Kædefald Højde mm	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Vægt kg	Forventet levering (dage)	
0208003	8717365258787	1	-	YA/1000KG	5.6 x 17.1	37	1	312	144	91	122	268	28	43	312	6,2	10
0208003-1.5	8717365258794	1	1,5	YA/1000KG/1,5M	5.6 x 17.1	37	1	312	144	91	122	268	28	43	312	6,2	2
0208003-3	8717365163715	1	3	YA/1000KG/3M	5.6 x 17.1	37	1	312	144	91	122	268	28	43	312	7,3	10

0208003-4.5	8717365264672	1	4,5	YA/1000KG/4,5M	5.6 x 17.1	37	1	312	144	91	122	268	28	43	312	8,4	10
0208003-6	8717365264689	1	6	YA/1000KG/6M	5.6 x 17.1	37	1	312	144	91	122	268	28	43	312	9,5	10
0208005	8717365258800	1,6	-	YA/1600KG	7.1 x 21	30	1	352	162	99	136	310	29	43	352	9,5	10
0208005-1.5	8717365258817	1,6	1,5	YA/1600KG/1,5M	7.1 x 21	30	1	352	162	99	136	310	29	43	352	9,5	10
0208005-3	8717365163722	1,6	3	YA/1600KG/3M	7.1 x 21	30	1	352	162	99	136	310	29	43	352	11,3	10
0208005-4.5	8717365264702	1,6	4,5	YA/1600KG/4,5M	7.1 x 21	30	1	352	162	99	136	310	29	43	352	13,1	10
0208005-6	8717365264719	1,6	6	YA/1600KG/6M	7.1 x 21	30	1	352	162	99	136	310	29	43	352	14,9	10
0208007	8717365260025	3,2	-	YA/3200KG	9.0 x 27.2	37	1	420	186,5	104	180	310	36	53	420	15,5	10
0208007-1.5	8717365260032	3,2	1,5	YA/3200KG/1,5M	9.0 x 27.2	37	1	420	186,5	104	180	310	36	53	420	15,5	10
0208007-3	8717365163739	3,2	3	YA/3200KG/3M	9.0 x 27.2	37	1	420	186,5	104	180	310	36	53	420	18,2	10
0208007-4.5	8717365264733	3,2	4,5	YA/3200KG/4,5M	9.0 x 27.2	37	1	420	186,5	104	180	310	36	53	420	20,9	10
0208007-6	8717365264740	3,2	6	YA/3200KG/6M	9.0 x 27.2	37	1	420	186,5	104	180	310	36	53	420	23,6	10
0208009	8717365260049	6,3	-	YA/6300KG	9.0 x 27.2	38	2	564	186,5	104	235	310	47	70	564	26,5	10
0208009-1.5	8717365260056	6,3	1,5	YA/6300KG/1,5M	9.0 x 27.2	38	2	564	186,5	104	235	310	47	70	564	26,5	10
0208009-3	8717365264757	6,3	3	YA/6300KG/3M	9.0 x 27.2	38	2	564	186,5	104	235	310	47	70	564	32	10
0208009-4.5	8717365264764	6,3	4,5	YA/6300KG/4,5M	9.0 x 27.2	38	2	564	186,5	104	235	310	47	70	564	37,5	10
0208009-6	8717365264771	6,3	6	YA/6300KG/6M	9.0 x 27.2	38	2	564	186,5	104	235	310	47	70	564	43	10
0208011	8717365260063	9	-	YA/9000KG	9.0 x 27.2	39	3	589	186,5	104	300	310	73	85	689	42	10
0208011-1.5	8717365260070	9	1,5	YA/9000KG/1,5M	9.0 x 27.2	39	3	589	186,5	104	300	310	73	85	689	42	10
0208011-3	8717365264788	9	3	YA/9000KG/3M	9.0 x 27.2	39	3	589	186,5	104	300	310	73	85	689	50,1	10
0208011-4.5	8717365264795	9	4,5	YA/9000KG/4,5M	9.0 x 27.2	39	3	589	186,5	104	300	310	73	85	689	58,2	10
0208011-6	8717365264801	9	6	YA/9000KG/6M	9.0 x 27.2	39	3	589	186,5	104	300	310	73	85	689	66,3	10

## Stregtegning

