

Universal Lifters Starcon

Product information

The Starcon universal lifting eye is made for lifting precast concrete elements together with spherical head anchors. The claw grips on to the head of the spherical head anchors.

The Starcon universal lifting eye has been load tested with up to 2 times of the working load limit (WLL). Unique or general certificate on request.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Material: Steel

Marking: CE-marked, UKCA-marked, Batch code, Load group, WLL, Starcon

Finish: Electro galvanized

Safety factor: 4:1

Note: The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contac<u>CERTEX Danmark A/S – Starcon</u> for information on the applicable delivery time.

Part Code	WLL ton	Load grp.	a mm	b mm	d mm	f mm	L mm	Weight kg	Delivery time
650210013001	1.3	1.3	73	43.5	34	70.5	186	0.95	2
650210025001	2.5	2.5	88	50	42	85	225	1.5	2
650210050001	5	5	110	67.5	55	88	282	3.18	100
650210100001	10	10	159	82	74	116	391	9.12	2
650210200001	20	20	183	106	110	123.5	490	20.2	2

Blueprint

