

Transport Anchor with cross hole Starcon

Product information

STARCON Transport Anchors with cross hole with inside thread for transport and fixing of concrete elements.

The transport anchor with cross hole can be used together with the reinforcement bar which is bent and mounted in the lower cross hole. Using a transport anchor with cross hole is one of the best ways of lifting and fixing concrete wall elements or tunnel elements.

Transport anchors with cross hole are also available with metric thread.

Material: Steel S355.

Marking: According to standard, Load Group+Starcon, batch code, CE.

Temperature range: 100°C. **Finish:** Electro-galvanized (silver).

Standard: CEN/TR 15728 - VDI/BV-BS 6205

Note: The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contacter Danmark

 $\underline{\text{A/S}-\text{Starcon}}$ for information on the applicable delivery time.

Subject to prior sale!

Part Code	Thread mm	Load grp. t	Length mm	L mm	Ø D mm	e mm	Øg mm	Thread mm	Weight kg	Delivery time
650530NK3010ZN	M10	0.4	50	50	13.2	22	10	M10	0.031	2
650530NK3012ZN	M12	0.5	60	60	15	25	10	M12	0.041	2
650530NK3016ZN	M16	1.2	79	79	21	32	13	M16	0.1	2
650530NK3020ZN	M20	2	99	99	27.5	37	15	M20	0.22	2
650530NK3024ZN	M24	2.5	110	110	31	40	18	M24	0.28	2

Blueprint

