



## STA-S Spread Anchor

### Product information

Transport Anchor STA-S is suitable for loads from 0.7 up to 22.0 t and for use in both thin panels and plates. The head of the spread anchor has a hole in which the locking bolt of the lifting eye is mounted. Other holes in the anchor are for further reinforcement.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

**Marking:** CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

**Finish:** Untreated or hot dip galvanized

**Note:** The delivery time for the individual products is estimated. If the desired quantity is not in stock, please contact [CERTEX Danmark A/S](#) – [Starcon](#) for information on the applicable delivery time.

Part Code	Load grp.	Lenght mm	Finish	L mm	a mm	b mm	c mm	Hole mm	Weight kg	Delivery time
65012202501501	2.5	150	Untreated	150	30	14	10	14x20	0.32	2
65012202501502	2.5	150	HDG	150	30	14	10	14x20	0.32	2
65012202502001	2.5	200	Untreated	200	30	14	10	14x20	0.42	2
65012205001801	5	180	Untreated	180	40	20	10	20x22	0.75	2
65012205001802	5	180	HDG	180	40	20	10	20x22	0.78	2
65012205002401	5	240	Untreated	240	40	20	10	20x22	1.01	2
65012205002402	5	240	HDG	240	40	20	10	20x22	1.05	2
65012207502601	7.5	260	Untreated	260	60	26	16	26x30	1.68	2
65012207502602	7.5	260	HDG	260	60	26	16	26x30	1.8	2
65012210003001	10	300	Untreated	300	60	28	20	28x30	2.65	2
65012210003002	10	300	HDG	300	60	28	20	28x30	2.65	2
65012214003701	14	370	Untreated	370	80	35	20	35x46	3.99	2
65012214003702	14	370	HDG	370	80	35	20	35x46	3.99	2
65012222005001	22	500	Untreated	500	90	35	26	35x46	8.12	2
65012222005002	22	500	HDG	500	90	35	26	35x46	8.16	100

# Blueprint

