



## STA-Z 2-Hole Anchor

### Product information

The 2-hole transport anchor STA-Z is suitable for loads from 0.7 up to 22.0 t. The STA-Z 2-hole anchor is almost similar to the transport anchor STA-S. The STA-Z 2-hole anchor, however, uses more reinforcement which is mounted through the lower hole. The head of the anchor has a hole in which the locking bolt of the ring clutch is mounted. Other holes in the anchor are meant for further reinforcement.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

**Marking:** CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

**Finish:** Untreated or hot dip galvanized

**Note:** The delivery time for the individual products is estimated. If the desired quantity is not in stock, please contact [CERTEX Danmark A/S](#) – [Starcon](#) for information on the applicable delivery time.

Part Code	Load grp.	Lenght mm	Finish	L mm	a mm	b mm	c mm	Hole mm	Weight kg	Delivery time
65012602500901	2.5	90	Untreated	90	30	14	10	14x20	0.16	2
65012602500902	2.5	90	HDG	90	30	14	10	14x20	0.17	2
65012605001201	5	120	Untreated	120	40	18	15	18x22	0.42	100
65012605001202	5	120	HDG	120	40	18	15	18x22	0.42	2
65012607501601	7.5	160	Untreated	160	60	26	16	26x30	0.91	2
65012607501602	7.5	160	HDG	160	60	26	16	26x30	0.92	2
65012610001701	10	170	Untreated	170	60	30	20	28x30	1.26	2
65012610001702	10	170	HDG	170	60	30	20	28x30	1.26	2
65012614002401	14	240	Untreated	240	80	35	20	35x46	2.36	2
65012614002402	14	240	HDG	240	80	35	20	35x46	2.36	2
65012622003001	22	300	Untreated	300	90	35	28	35x46	4.74	2
65012622003002	22	300	HDG	300	90	35	28	35x46	4.74	2
65012626003001	26	300	Untreated	300	120	65	30	35x45	6.2	2
65012626003002	26	300	HDG	300	120	65	30	35x45	6.25	2

# Blueprint

