



STA-SA Universal and Erection Anchor Conical

Product information

The Transport Anchor STA-SA - CONIC is suitable for loads from 0.7 up to 22.0 t. The conical transport anchor is designed for the tipping of panels from a horizontal to a vertical position. The conical anchor is used for erection and turning of precasted thin wall units in both directions. The head of the anchor has a hole in which the locking bolt of the lifting eye is mounted. Other holes in the anchor are meant for further reinforcement. The head of the anchor is designed so that the load cannot be transferred to the upper part of the concrete surface.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

Finish: Untreated or hot dip galvanized

Note: The delivery time for the individual products is estimated. If the desired quantity is not in stock, please contact [CERTEX Danmark A/S](#) – [Starcon](#) for information on the applicable delivery time.

Part Code	Load grp. t	Length mm	Finish	L mm	a mm	b mm	c mm	g mm	Hole mm	Weight kg	Delivery time
65012302502301	2.5	230	Untreated	230	55	14	10	45	14x20	0.66	100
65012302502302	2.5	230	HDG	230	55	14	10	45	14x20	0.66	2
65012304002701	4	270	Untreated	270	70	18	10	70	18x22	1.5	2
65012305002901	5	290	Untreated	290	70	20	15	70	20x22	1.71	2
65012305002902	5	290	HDG	290	70	20	15	70	20x22	1.86	2
65012307503201	7.5	320	Untreated	320	95	26	15	90	26x30	2.36	2
65012307503202	7.5	320	HDG	320	95	26	15	90	26x30	2.51	2
65012310003901	10	390	Untreated	390	95	28	20	90	28x30	4.1	2
65012310003902	10	390	HDG	390	95	28	20	90	28x30	4.1	2
65012312505002	12.5	500	HDG	500	150	35	20	90	35x45	8.24	2

Blueprint

