



STA-SE Universal and Erection Anchor - one side

Product information

The Transport anchor STA-SE is suitable for loads from 0.7 up to 22.0 t. The transport anchor STA-SE is designed for the tipping of panels from a horizontal to a vertical position. The anchor is used for erecting and turning precasted thin wall units in one direction. The head of the anchor has a hole in which the locking bolt of the ring clutch is mounted. Other holes in the anchor are meant for further reinforcement. The head of the anchor is designed so that the load cannot be transferred to the upper part of the concrete surface.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

Finish: Untreated or hot dip galvanized

Note: The delivery time for the individual products is estimated. If the desired quantity is not in stock, please contact [CERTEX Danmark A/S](#) - [Starcon](#) for information on the applicable delivery time.

Part Code	Load grp. t	Lenght mm	Finish	c mm	L mm	a mm	g mm	r mm	Weight kg	Delivery time
65012402502301	2.5	230	Untreated	10	230	40	45	14x20	0.63	2
65012405002901	5	290	Untreated	15	290	55	44	20x22	1.64	2
65012407503201	7.5	320	Untreated	15	320	80	90	26x30	2.65	2
65012410003901	10	390	Untreated	20	390	80	90	26x30	4.42	2

Blueprint

