



Ring Clutch Starcon

Product information

The ring clutch is used for lifting and transport of the transport anchor system STA (Transport Anchors STA-S, STA-Z, STA-SA, STA-SE, Sandwich Panel Anchor STA-ST, Plate Anchor STA-P or Flat Foot Anchor STA-F). Load of the ring clutch can be made from all directions. The head of the coupling incorporates with a locking bolt which is attached to the anchor.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Material: Steel

Marking: CE-marked, UKCA-marked, Batch code, Load group, WLL, Starcon

Finish: Electro galvanized

Safety factor: 4:1

Note: The delivery time for the individual products is estimated. If the desired quantity is not in stock, please contact [CERTEX Danmark A/S – Starcon](#) for information on the applicable delivery time.

Part Code	WLL ton	Load grp.	a mm	b mm	c mm	d mm	L mm	t mm	Weight	Delivery time
650290025001	2.5	2.5 t	70	58	80	27	265	12	0.95	2
650290050001	5	5 t	86	65	105	36	330	16	1.5	2
650290100001	10	10 t	112	90	150	50	425	25	3.18	2

Blueprint

