



Power Sling Shackle Green Pin® P-6043

Product information

Sling shackel with a revolutionary design. Save up to 20% on synthetic- and wire rope costs, with the optimal D/d ratio.

Certification: At no extra charges this product can be supplied with a works certificate, material certificate, manufacturer test certificate, EC Declaration of Conformity. All shackles from 125 t are be supplied with Lloyd's Register of Shipping Certificate on proof load. Supplied on request: An MPI and/or US inspection certificate.

Material: Bow and pin alloy steel, quenched and tempered

Marking: CE-marked

Temperature range: -40°C up to +200°C

Finish: Shackle bow painted silver, pin painted green

Safety factor: 5:1

Grade: 8

Part Code	WLL ton	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm	l mm	Weight kg	Delivery time
420112500960	125	80	166	85	134	364	220	631	382	370	36	205	95	10
420115000960	150	95	182	90	144	389	250	703	408	420	42	248	134	10
420120000960	200	105	204	100	154	479	276	838	446	475	47	290	195	10
420125000960	250	120	238	110	174	539	300	938	503	515	60	314	271	10
420130000960	300	134	260	121	189	599	350	1.031	550	605	60	345	368	10
420140000960	400	160	305	140	224	620	370	1.078	645	652	80	392	563	10
420150000960	500	180	340	152	255	679	450	1.239	714	763	85	440	786	10
420160000960	600	200	365	170	280	739	490	1.353	788	820	90	475	1.009	10
420112500961	1,250	300	470	245	442	928	650	1.812	1,164	1,144	140	670	2.933	10

Blueprint

