



Offshore crane



Deck crane



Steel wire rope Vero 4

Product information



Wire rope construction: Vero 4 is a 4-strand rotation resistant rope with compacted strands. It has a high breaking load and is particularly suitable for harshest working conditions with dynamic impact loads.

Features:

- High breaking strength.
- Very robust rope construction.
- Offers excellent resistance against crushing and abrasion.

ISO 4309 Rope Category No: All Diameters **RCN.22**

Marking: According to standard

Standard: EN 12385-4

Warning: Vero 4 may not be used with a swivel.

Fill factor: 0.631

RCN: 22

Tolerance Ø: +2% to +4%

Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Steel area mm ²	Min. Breaking force kN.	Finish	Weight kg/100m	Delivery time
103100803270499	8	1,960	-	-	Galvanized	-	-
103100903270499	9	1,960	-	-	Galvanized	-	-
103101003270499	10	1,960	-	-	Galvanized	-	-
103101103270499	11	1,960	-	-	Galvanized	-	-

103101203270499	12	1,960	-	-	Galvanized	-	-
103101303270499	13	1,960	-	-	Galvanized	-	-
103101403270499	14	1,960	-	-	Galvanized	-	-
103101503270499	15	1,960	-	-	Galvanized	-	-
103101603270499	16	1,960	-	-	Galvanized	-	-
103101803270499	18	1,960	-	-	Galvanized	-	-
103101903270499	19	1,960	-	-	Galvanized	-	-
103102003270499	20	1,960	-	-	Galvanized	-	-
103102203270499	22	1,960	-	-	Galvanized	-	-
103102403270499	24	1,960	-	-	Galvanized	-	-
103102503270499	25	1,960	-	-	Galvanized	-	-
103102603270499	26	1,960	-	-	Galvanized	-	-
103102703270499	27	1,960	-	-	Galvanized	-	-
103102803270499	28	1,960	-	-	Galvanized	-	-
103102903270499	29	1,960	-	-	Galvanized	-	-
103103003270499	30	1,960	-	-	Galvanized	-	-
103103103270499	31	1,960	-	-	Galvanized	-	-
103103203270499	32	1,960	-	-	Galvanized	-	-
103103303270499	33	1,960	-	-	Galvanized	-	-
103103353270499	33.5	1,960	-	-	Galvanized	-	-
103103403270499	34	1,960	-	-	Galvanized	-	-
103103503270499	35	1,960	-	-	Galvanized	-	-
103103603270499	36	1,960	-	-	Galvanized	-	-

Technical data