



Eye Self Locking Hook XLO, Green Pin®

Product information

The Green Pin® Self-Locking Hook E EN1677-3 is a grade 8 eye self-locking hook according to European standard for components for sling EN 1677-3. The self-locking hook locks automatically as soon as it is brought under tension. To release the load the user must manually unlock the hook, which prevents unintended release. This hook brings a full safety for lifting as the latch cannot be removed. The eye of the hook can be connected to grade 8 chain with a connecting link, to a webbing with a web sling connector or to a wire rope with a thimble. The flat on the eye enables the assembly with an omega link or on a thimble. The Green Pin® Self-Locking Hook E EN1677-3 is available in a range to suit 5/6 mm up to 18/20 mm grade 8 chain.

Certification: At no extra charge this product can be supplied with a works certificate, a 3.1 material certificate and/or EC Declaration of Conformity.

Material: Alloy steel, quenched and tempered.

Marking: According to standard

Temperature range: -40°C up to +200°C

Finish: painted yellow (J), red (R) or white

Standard: EN 1677-3

Note: From 12.8 t without flat part.

Safety factor: 4:1

Grade: 8

Part Code	Chain diameter mm	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	i mm	j mm	Weight kg	Delivery time
401300110440	5-6	1.12	111	24	32	16	26	47	77	147	11	7	0.51	2
401300200440	7-8	2	134	29	43	23	29	57	92	176	14	7	0.91	10
401300320440	10	3.2	168	35	47	32	35	69	111	219	17	10	1.79	2
401300540440	13	5.4	199	46	61	37	45	87	142	264	20	13	3.36	10
401300820440	16	8.2	247	59	74	43	56	111	185	328	26	16	7	2
401301280440	18-20	12.8	282	69	88	51	63	126	207	375	28	20	9.22	2

Blueprint

