



Mobile crane



Piling crane



Steel Wire Rope verotop S

Product information



Wire rope construction: verotop S is a very flexible rotation-resistant rope with compacted outer strands and very high breaking strength.

Features:

- Very strong compacted rotation-resistant rope.
- Achieves very good bending fatigue results.
- Offers excellent resistance to crushing and abrasion.
- Possesses perfect spooling behavior on multilayer drum.

ISO 4309 Rope Category No: All Diameters **RCN.23-2.**

Marking: According to standard

Standard: EN 12385-4

Note: verotop S can be used either with or without swivel.

Fill factor: 0.742

RCN: 23-2

Tolerance Ø: +2% to +4%

Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Steel area mm ²	Min. Breaking force kN.	Finish	Weight kg/100m	Delivery time
104101305070159	13	1,960	-	-	Bright	-	-
104101405070159	14	1,960	-	-	Bright	-	-
104101505070159	15	1,960	-	-	Bright	-	-
104101605070159	16	1,960	-	-	Bright	-	-

104101705070159	17	1,960	-	-	Bright	-	-
104101805070159	18	1,960	-	-	Bright	-	-
104101905070159	19	1,960	-	-	Bright	-	-
104102005070159	20	1,960	-	-	Bright	-	-
104102105070159	21	1,960	-	-	Bright	-	-
104102205070159	22	1,960	-	-	Bright	-	-
104102245070159	22.4	1,960	-	-	Bright	-	-
104102305070159	23	1,960	-	-	Bright	-	-
104102405070159	24	1,960	-	-	Bright	-	-
104102505070159	25	1,960	-	-	Bright	-	-
104102545070159	25.4	1,960	-	-	Bright	-	-
104102605070159	26	1,960	-	-	Bright	-	-
104102705070159	27	1,960	-	-	Bright	-	-
104102805070159	28	1,960	-	-	Bright	-	-
104102865070159	28.6	1,960	-	-	Bright	-	-
104102905070159	29	1,960	-	-	Bright	-	-
104103005070159	30	1,960	-	-	Bright	-	-
104103105070159	31	1,960	-	-	Bright	-	-