



## Web Sling Connector X-016

### Product information

At least 25% greater WLL than traditional Grade 8 products.  
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.  
Fatigue rated to 20,000 cycles at 1.5 times the WLL.  
Tempering temperature minimum 400°C

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 10

Part Code	Chain diameter mm	WLL ton	EWL mm	A mm	B mm	D mm	K mm	W mm	Weight kg	Delivery time
402200140200	6	1.4	55	15	17	7	56	39	0.2	10
402200250200	7-8	2.5	62	18	23	9	63	39	0.3	2
402200400200	10	4	78	25	27	11	77	46	0.6	10
402200670200	13	6.7	95	30	37	16	97	53	1.1	2
402201000200	16	10	115	36	39	19	114	66	2	2
402201600200	20	16	132	42	46	22	132	79	3.2	2
402201900200	22	19	187	49	59	24	188	124	7.7	10

## Blueprint

