



Clevis Sling Hook X-043/S Grade 10

Product information

At least 25% greater WLL than traditional Grade 8 products.
 Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
 Tempering temperature minimum 400°C.
 Magnaflux crack detection is performed 100% on each batch.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-2

Safety factor: 4:1

Grade: 10

| Part Code | WLL ton | EWL mm | For Grade 100 Chain mm | A mm | H mm | K mm | P1 mm | T mm | Weight kg | Delivery time |
|--------------|---------|--------|------------------------|------|------|------|-------|------|-----------|---------------|
| 402300140700 | 1.4 | 79 | 6 | 7 | 18 | 79 | 23 | 15 | 0.3 | 10 |
| 402300250700 | 2.5 | 98 | 7, 8 | 9 | 22 | 98 | 27 | 18 | 0.6 | 2 |
| 402300400700 | 4 | 122 | 10 | 12 | 30 | 122 | 34 | 24 | 1.1 | 2 |
| 402300670700 | 6.7 | 147 | 13 | 15 | 37 | 147 | 44 | 30 | 2.3 | 2 |
| 402301000700 | 10 | 166 | 16 | 17 | 41 | 166 | 48 | 39 | 3.8 | 2 |
| 402301600700 | 16 | 207 | 20 | 24 | 64 | 207 | 57 | 48 | 8.7 | 2 |
| 402301900700 | 19 | 217 | 22 | 25 | 61 | 217 | 73 | 52 | 9.5 | 2 |

Blueprint

