



Eye Foundry Hook X-047

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Testing according to DIN PAS 1061 and ASTM A952/A 952M.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Designed for the assembly of chain slings where wide throat openings are necessary

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Standard: EN 1677-1

Warning: Before using the hook, check whether hooks without safety latches are allowed to be used for the particular application.

Safety factor: 4:1

Grade: 10

| Part Code | Chain diameter mm | WLL ton | EWL mm | A mm | D mm | H mm | K mm | P mm | T mm | Weight kg | Delivery time |
|--------------|----------------------|------------|-----------|---------|---------|---------|---------|---------|---------|--------------|---------------|
| 402300250800 | 7-8 | 2.5 | 123 | 24 | 12 | 30 | 123 | 62 | 19 | 0.8 | 2 |
| 402300400800 | 10 | 4 | 149 | 32 | 15 | 35 | 149 | 74 | 23 | 1.6 | 10 |
| 402300670800 | 13 | 6.7 | 180 | 40 | 19 | 39 | 180 | 88 | 32 | 2.6 | 2 |
| 402301000800 | 16 | 10 | 213 | 50 | 25 | 46 | 213 | 98 | 41 | 4.5 | 10 |
| 402301600800 | 20 | 16 | 248 | 60 | 26 | 59 | 248 | 113 | 58 | 9.3 | 10 |

Blueprint

