



Connecting link X-015 Grade 10

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Suitable for use with both Grade 8 and Grade 10 chain.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

| Part Code | Chain diameter mm | WLL ton | EWL mm | A mm | B mm | D mm | K mm | Weight kg | Delivery time |
|--------------|----------------------|------------|-----------|---------|---------|---------|---------|--------------|---------------|
| 402200140190 | 6 | 1.4 | 45 | 15 | 17 | 7 | 45 | 0.08 | 2 |
| 402200250190 | 7-8 | 2.5 | 59 | 18 | 23 | 9 | 59 | 0.2 | 2 |
| 402200400190 | 10 | 4 | 69 | 25 | 27 | 11 | 69 | 0.3 | 2 |
| 402200670190 | 13 | 6.7 | 92 | 30 | 37 | 16 | 92 | 0.7 | 2 |
| 402201000190 | 16 | 10 | 101 | 36 | 39 | 19 | 101 | 1.2 | 2 |
| 402201600190 | 20 | 16 | 122 | 42 | 46 | 23 | 122 | 2.1 | 2 |
| 402201900190 | 22 | 19 | 152 | 49 | 59 | 24 | 152 | 3.5 | 2 |
| 402202650190 | 26 | 26.5 | 162 | 55 | 62 | 30 | 162 | 4.8 | 2 |
| 402204000190 | 32 | 40 | 203 | 69 | 79 | 36 | 203 | 9 | 2 |

Blueprint

