



Welded Master Link X-002W

Product information

- Welded Master Link designed for 1-2 legs Wire Rope and Chain Slings.
- At least 25% greater WLL than traditional Grade 8 products.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

| Part Code | Code | WLL ton | EWL mm | For chain gr 10 Ø 2 leg mm | For chain gr 10 Ø 1 leg mm | Din 15401.NO | D mm | A mm | B mm | Weight kg | Delivery time |
|--------------|-------|---------|--------|----------------------------|----------------------------|--------------|------|------|------|-----------|---------------|
| 402100280500 | CD-13 | 2.8 | 120 | 6 | 7,8 | 4 | 13 | 120 | 70 | 0.4 | 2 |
| 402100400500 | CD-16 | 4 | 140 | 7,8 | 10 | 5 | 16 | 140 | 80 | 0.7 | 2 |
| 402100670500 | CD-19 | 6.7 | 160 | 10 | 13 | 6 | 19 | 160 | 95 | 1.1 | 2 |
| 402100850500 | CD-22 | 8.5 | 170 | 10 | 13 | 10 | 22 | 170 | 105 | 1.6 | 10 |
| 402101150500 | CD-28 | 11.5 | 190 | 13 | 16 | 10 | 28 | 190 | 110 | 2.9 | 2 |
| 402101700500 | CD-32 | 17 | 230 | 16 | 20 | 12 | 32 | 230 | 130 | 4.5 | 2 |
| 402102510500 | CD-36 | 25.1 | 275 | 20 | 22 | 20 | 36 | 275 | 150 | 6.7 | 2 |

Blueprint

