

## Portable Davit Crane 5PF5



### Product information

#### 225 kg capacity portable Davit Crane

- Load ratings up to 385 kg
- Portable, heaviest part 13,2 kg
- Rugged and affordable
- Manual or power winch operation (E2)
- 360° rotation
- Boom adjustable in three positions
- Easy, No-Tools Assembly/Disassembly (all individual components less than 13,5 kg)
- Variety of bases
- 2-Year warranty
- Proof of load 125% of WLL (Optional)

Machinery directive: 2006/42/EC as amended by Directive 95/16/EC.

**Marking:** CE-marked

**Finish:** Powder coat

**Note:** Five corrosion-resistant surfaces (powder coating (5PT20), galvanized (5PT20G), stainless 304 (S) and 316 (S316) and three layers of epoxy)

| Part Code   | Code     | WLL<br>ton | Weight<br>kg | Delivery time |
|-------------|----------|------------|--------------|---------------|
| 60115PF5M1  | 5PF5-M1  | 0.225      | 34.5         | 10            |
| 60115PF5GM1 | 5PF5G-M1 | 0.225      | 34.5         | 10            |
| 60115PF5E2  | 5PF5-E2  | 0.225      | 65.5         | 10            |
| 60115PF5SM3 | 5PF5S-M3 | 0.385      | 38           | 10            |
| 60115PF5M2  | 5PF5-M2  | 0.385      | 46           | 10            |
| 60115PF5GM2 | 5PF5G-M2 | 0.385      | 46           | 10            |

## Technical data

**First Mate, 5PF5, with Pedestal Base**

| <b>Boom Position</b> | <b>Load Rating (KG)</b> | <b>Hook Reach (mm)</b> | <b>Hook height (mm)*</b> |
|----------------------|-------------------------|------------------------|--------------------------|
| A                    | 225                     | 1066                   | 1016                     |
| B                    | 225                     | 889                    | 1524                     |
| C                    | 225                     | 609                    | 1778                     |

\* Optional Base extension can provide 380mm more hook height

**First Mate, 5PF5 with Flush or Wall base**

| <b>Boom Position</b> | <b>Load Rating (KG)</b> | <b>Hook Reach (mm)</b> | <b>Hook height (mm)*</b> |
|----------------------|-------------------------|------------------------|--------------------------|
| A                    | 225                     | 1066                   | 660                      |
| B                    | 225                     | 889                    | 1168                     |
| C                    | 225                     | 609                    | 1422                     |

\* Optional Base extension can provide 380mm more hook height

# Blueprint

