



Clevis Sling Hook Tyacan® UCSCT

Product information

Clevis sling hook with a safety latch that prevents the sling from sliding back.

Material: Alloy steel.

Marking: According to standard, Manufacturer ID, chain diameter, traceability code, steel grade, item code and origin.

Temperature range: -40°C up to 200°C.

Finish: Blue painted.

Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

| Part Code | WLL ton | LC kN | Type | a mm | b mm | c mm | d mm | e mm | f mm | g mm | h mm | i mm | Weight kg | Delivery time |
|--------------|---------|-------|-------|-------|------|------|------|------|------|-------|-------|------|-----------|---------------|
| 402300260880 | 2.6 | 52 | UCSCT | 112 | 17 | 30 | 20 | 24 | 44 | 87 | 158 | 13 | 0.73 | 10 |
| 402300400880 | 4 | 80 | UCSCT | 129 | 22 | 33 | 24 | 29 | 57 | 106 | 186 | 16 | 1.31 | 10 |
| 402300500880 | 5 | 100 | UCSCT | 125.6 | 24 | 37 | 28.6 | 34.6 | 68 | 123.4 | 219.7 | 20 | 2.15 | 10 |
| 402300680880 | 6.8 | 136 | UCSCT | 159 | 32 | 37 | 32 | 39 | 74 | 133 | 235 | 20 | 2.56 | 10 |

Blueprint

