



Swivel Self Locking Hook X-027N

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Rotate when loaded.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Built with ball bearing and enables full swivel feature under load.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard

Temperature range: Tempering temperature minimum 400°C .

Finish: Blue painted.

Standard: EN 1677-3

Safety factor: 4:1

Grade: 10

Part Code	Chain diameter mm	WLL ton	EWL mm	A mm	B mm	D mm	H mm	K mm	P mm	T mm	Weight kg	Delivery time
420500140950	6	1.4	149	32	23	12	19	149	28	15	0.7	2
420500250950	7-8	2.5	186	36	29	13	24	186	34	20	1.2	2
420500400950	10	4	218	41	35	16	30	218	44	26	2	10
420500670950	13	6.7	276	46	44	21	39	276	51	30	4.1	10
420501000950	16	10	329	61	50	23	49	329	60	36	7.2	2
420501600950	20	16	387	74	82	25	65	403	70	53	13	2
420501900950	22	19	457	97	96	33	63	454	80	49	20	2
420502650950	26	26.5	535	123	116	51	69	535	99	56	33	10

Blueprint

