



Swivel Jaw End Crosby G-403

Product information

Chain swivels with out bearing. According to Federal Specification RR-C-271F.

Material: Hot dip Galvanized - Quenched & Tempered

Marking: CE-marked, WLL

Finish: Galvanized

Note: The swivels are positioning devices and are not intended to rotate under load. For load swivels, see ball bearing swivels.

Safety factor: 5:1

Part Code	Diameter mm	WLL ton	A mm	B mm	C mm	G mm	J mm	K mm	L mm	M mm	N mm	P mm	R mm	U mm	V mm	Weight kg	Delivery time
422500390130	6	0.39	31.8	17.5	19.1	17.5	17.5	11.9	26.2	7.9	22.4	6.4	67	42.9	42.9	0.1	10
422500060130	8	0.57	41.4	20.6	25.4	20.6	20.6	12.7	28.7	9.7	22.4	7.9	74.5	52	46	0.15	10
422500100130	10	1.02	51	23.9	31.8	25.4	25.4	16	35.8	12.7	26.9	9.7	92	63.5	57	0.3	10
422500160130	13	1.63	63.5	33.3	38.1	33.3	33.3	19.1	44.5	16	33.3	12.7	114	81	73	0.61	10
422500240130	16	2.36	76	39.5	44.5	41.4	38.1	23.9	52	19.1	38.1	16	135	98.5	87.5	1.12	10
422500330130	19	3.27	89	44.5	51	47.8	47.8	28.7	64.5	22.4	44.5	19.1	154	109	102	1.76	10
422500450130	22	4.54	102	52	57	54	54	34	70.9	25.4	52	22.4	178	127	115	2.66	10
422500570130	25	5.67	114	58.5	63.5	67	60.5	44.5	94.5	28.7	71.5	28.7	217	146	151	4.46	10
422500820130	32	8.16	145	68.5	79.5	79.5	76	52	109	41.4	71.5	35.1	248	179	162	7.14	10
422502050130	38	20.5	178	98.5	102	143	102	73	152	57	113	57	362	254	275	24.8	10

Blueprint

