

## Rigging Screw Gunnebo No. 801 Jaw-Jaw

### Product information



**Standard:** Working load acc. to U.S. Fed.spec.FF-T-791.b. Supplied with closed body from 2,5-17 T, larger dimensions open body.

**Material:** Quenched and tempered alloy steel.

**Temperature range:** -20°C up to +200°C

**Finish:** Hot dip galvanized.

**Safety factor:** 5:1

| Part Code    | WLL ton | Tensioning length | Thread M/UNC | B mm | F mm | G mm | H mm | K mm | L mm | M mm | N mm  | Weight kg | Delivery time |
|--------------|---------|-------------------|--------------|------|------|------|------|------|------|------|-------|-----------|---------------|
| 422100250360 | 2.5     | 210               | M20          | 270  | 13   | 21   | 45   | 20   | 16   | 50   | 455   | 2.3       | 10            |
| 422100500360 | 5       | 250               | M24          | 340  | 19   | 28   | 56   | 28   | 22   | 65   | 570   | 4.6       | 10            |
| 422100700360 | 7       | 270               | 1 1/4"       | 370  | 22   | 35   | 70   | 38   | 28   | 85   | 680   | 8         | 10            |
| 422101000360 | 10      | 300               | 1 1/2"       | 400  | 25   | 40   | 78   | 45   | 32   | 100  | 790   | 14        | 10            |
| 422101300360 | 13      | 360               | 1 3/4"       | 500  | 30   | 45   | 90   | 50   | 39   | 105  | 870   | 24        | 10            |
| 422101700360 | 17      | 450               | 2"           | 600  | 35   | 45   | 100  | 58   | 45   | 120  | 1,030 | 38        | 10            |

# Blueprint

