



General use



## Steel Wire Rope PVC-coated 6x7-WSC Stainless

### Product information



A stainless rope equipped with a Steel (WSC) and has a PVC-coating. It can be used for various applications such as locking rope, signaling devices, etc but not for lifting.

The PVC-coating is UV stabilized which makes it suitable for longterm outdoor use and it is fully compliant with REACH Directive 1907/2006.

**Rope construction:** 6x7-WSC

**Material:** AISI 316 / EN 1.4401

**Marking:** According to standard

**Temperature range:** -30°C up to +70°C

**Finish:** PVC-coated, see table for colour

**Standard:** EN 12385-4

*except material and coating*

**Note:** Peel off coating at end when making any end fittings such as clamping ferrules etc

**Fill factor:** 0,55

Part Code	Rope Diameter, mm	Inner diameter mm	Tensile strength N/mm <sup>2</sup>	Steel area mm <sup>2</sup>	Min. Breaking force kN	Colour	Finish	Rope lay.	Weight kg/100m	Delivery time
105120300200180	3	2	1,570	1.73	2.44	transparent	Stainless	sZ	2	2
105120400300180	4	3	1,570	3.89	5.48	transparent	Stainless	sZ	4.2	2
105120500400180	5	4	1,570	6.91	9.75	transparent	Stainless	sZ	7.3	10