



Polypropylene Fibre Rope 3-Strand

Product information

General purpose rope for a variety of marine applications; mooring, towing, fishing, pick-up lines, lifting slings, general purpose use. Resistant to rot, most acids and alkalis. The fibre is UV-stabilized against sunlight.

Standard length: 220m : 4-16mm spool - 18-48mm coil

Specific gravity: 0,91 (floats).

Melting point: Approx. 165°C.

Elongation: Approx. 30%.

Strength wet/dry: 100%.

Shock absorption: Very good.

Water absorption: None.

Abrasion resistance: Good.

Features: Spliced fibre.

Material: Polypropylene.

Marking: According to standard

Finish: Orange. Other colours possible on request.

Standard: EN ISO 1346

| Part Code | Diameter mm | Length m | MBL kN | Rope ends | Weight kg/220m | Delivery time |
|-----------------|-------------|----------|--------|------------|----------------|---------------|
| 300300602200130 | 6 | 220 | 5.4 | Plain ends | 3.7 | 2 |
| 300300802200130 | 8 | 220 | 9.4 | Plain ends | 6.6 | 10 |
| 300301202200130 | 12 | 220 | 19.9 | Plain ends | 14.5 | 10 |
| 300301602200130 | 16 | 220 | 34.3 | Plain ends | 25.5 | 10 |