

Ferrule TKH Talurit®



Product information

The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

Conical ferrule with an inspection hole to ensure the short end of the wire rope is correctly positioned after swaging. This hole remains open after swaging, due to the pressing in a die with a blind tap.

The ferrules can be used for fibre core, single layer wire ropes, steel core single layer wire ropes, rotation resistant wire ropes and some spiral strand ropes.

Material: Aluminium

Marking: According to standard

Standard: EN 13411-3

except size range

Note: See the manufacturer's product data sheet below for guidance on dimension selection.

Part Code	Ferrule size mm	Length mm	Delivery time
120100800200	8	36	10
120100900200	9	40	2
120101000200	10	45	2
120101100200	11	50	2
120101200200	12	54	2
120101300200	13	59	2
120101400200	14	63	2

120101600200	16	72	2
120101800200	18	81	2
120102000200	20	90	2
120102200200	22	99	2
120102400200	24	108	2
120102600200	26	117	2
120102800200	28	126	2
120103000200	30	135	10
120103200200	32	144	2
120103400200	34	153	2
120103600200	36	162	2
120103800200	38	171	2
120104000200	40	180	10
120104400200	44	198	2
120105000200	50	228	2
120105400200	54	246	2