



Eyebolt

Product information

For a maximum angle of use 90° between the two legs - divide the WLL by two.
Stated WLL is at 0°.

Material: Alloy steel.

Marking: According to standard, CE-marked, WLL, sizes, steel quality, productname, traceable.

Finish: Red painted.

Standard: ISO 3266

Note: Approved for lifting.

Safety factor: 4:1.

Part Code	WLL ton	Thread	Tightening torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	L mm	Weight kg	Delivery time
421100040030	0.4	M8	8	19.5	35.5	20	8	6	8	44	24	0.06	2
421100070030	0.7	M10	16	23	43	21	10	7	10	51	28	0.08	2
421100100030	1	M12	28	29	53	22	12	8	12	64	40	0.14	2
421100120030	1.2	M14	54	31.5	59.5	26	14	9	14	72	40	0.2	2
421100150030	1.5	M16	70	36	64	38	16	10	14	79	51	0.3	2
421100250030	2.5	M20	135	45.5	77.5	32	20	12	18	95	56	0.5	2
421100400030	4	M24	230	53	94	38	24	12	20.5	110	67	0.92	10

Technical data

	<input type="checkbox"/>	<input type="checkbox"/>		
	1	2		
	0°	0°		
Size	Single-leg	2-legs		
M8X24	0,4	0,8		
M10X28	0,7	1,4		
M12X40	1,0	2,0		
M14X40	1,2	2,4		
M16X51	1,5	3,0		
M20X56	2,5	5,0		
M24X67	4,0	8,0		

Blueprint

