



## Eye Nut 802

### Product information

Eye nut to be screwed by hand.

**Material:** Alloy steel 8.8.

**Marking:** Marked with WLL, sizes, steel quality, CE, producername, tracability.

**Finish:** Red painted.

**Note:** Approved for lifting.

**Safety factor:** 4:1

Part Code	WLL ton	Thread mm	A mm	B mm	C mm	E mm	F mm	H mm	Weight kg	Delivery time
421100040120	0.4	M6	25	45	25	10	10	45	0.1	2
421100080120	0.8	M8	25	45	25	10	10	45	0.1	2
421100100120	1	M10	25	45	25	10	10	45	0.1	2
421100160120	1.6	M12	35	63	35	14	14	62	0.26	2
421100300120	3	M14	35	63	35	14	14	62	0.26	2
421100400120	4	M16	35	63	35	14	14	62	0.26	2
421100500120	5	M18	50	90	50	20	20	90	0.75	2
421100600120	6	M20	50	90	50	20	20	90	0.75	2
421100800120	8	M24	50	90	50	20	20	90	0.75	10
421101000120	10	M27	60	108	65	24	24	109	1.4	10
421101200120	12	M30	60	108	65	24	24	109	1.4	2

## Technical data

	0°	0°	0°-45°	45°-60°	0°-45°	45°-60°
	WLL tons					
Size	Single-leg	2-leg	2-leg		3- or 4-leg	
M6	0,4	0,8	0,14	0,1	0,2	0,14
M8	0,8	1,6	0,28	0,2	0,4	0,28
M10	1,0	2,0	0,35	0,25	0,5	0,35
M12	1,6	3,2	0,56	0,4	0,8	0,56
M14	3,0	6,0	1,0	0,75	1,5	1,0
M16	4,0	8,0	1,4	1,0	2,0	1,4
M18	5,0	10	1,8	1,25	2,5	1,8
M20	6,0	12	2,1	1,5	3,0	2,1
M24	8,0	16	2,8	2,0	4,0	2,8
M27	10	20	3,5	2,5	5,0	3,5
M30	12	24	4,2	3,0	6,0	4,2

# Blueprint

