



Stud Link Chaincables

Product information

Stud link chain cables are stronger than coil chain, due to the studs across the inside width of each link. The studs add weight to the chain, it prevents the link from kinking and deform. Therefore stud link chains are preferred as anchor and cable chains on ships.

Our stud link chain cables are available in max. standard lengths of 27,5 m.

Other shorter chain lengths on request.

Grade 1 Breakload kN	Grade 2 Breakload kN	Grade 3 Breakload kN	ORQ Breakload kN	R3 Breakload kN	R4 Breakload kN	Number of links per 27,5 m	Delivery time
66	92	-	-	-	-	549	10
82	116	-	-	-	-	491	10
107	150	-	-	-	-	429	10
127	179	-	-	-	-	391	10
150	211	-	324	342	420	357	10
175	244	349	376	397	488	329	10
200	280	401	431	456	560	305	10
237	332	476	511	541	664	285	10

278	389	556	598	635	776	259	10
321	449	642	691	730	897	245	10
368	514	735	790	835	1.026	225	10
417	583	833	895	946	1.163	213	10
468	655	937	1.007	1.064	1.308	195	10
523	732	1.05	1.124	1.188	1.46	187	10
581	812	1.16	1.248	1.319	1.621	179	10
640	896	1.28	1.377	1.456	1.789	171	10
703	981	1.4	1.513	1.599	1.964	165	10
769	1.08	1.54	1.654	1.748	2.147	153	10
837	1.17	1.68	1.8	1.903	2.338	147	10
908	1.27	1.81	1.952	2.063	2.535	143	10
981	1.37	1.96	2.11	2.23	2.74	137	10
1.06	1.48	2.11	2.273	2.402	2.952	129	10
1.14	1.59	2.27	2.441	2.58	3.17	125	10
1.22	1.71	2.43	2.615	2.764	3.396	123	10
1.29	1.81	2.6	2.794	2.953	3.628	119	10
1.38	1.94	2.77	2.978	3.147	3.867	113	10
1.47	2.06	2.94	3.166	3.347	4.112	111	10
1.56	2.19	3.13	3.36	3.551	4.364	107	10
1.66	2.31	3.3	3.559	3.761	4.621	105	10
1.75	2.45	3.5	3.762	3.976	4.885	99	10
1.84	2.58	3.69	3.97	4.196	5.156	97	10

1.99	2.79	3.99	4.291	4.535	5.572	93	10
2.15	3.01	4.3	4.621	4.884	6.001	89	10
2.26	3.16	4.5	4.847	5.123	6.295	87	10
1.41	3.38	4.82	5.194	5.49	6.745	85	10
2.58	3.61	5.16	5.55	5.866	7.208	81	10
2.75	3.85	5.5	5.916	6.252	7.682	79	10
2.92	4.09	5.84	6.289	6.647	8.167	77	10
3.04	4.26	6.08	6.544	6.916	8.497	73	10
3.23	4.51	6.44	6.932	7.326	9.001	71	10
3.34	4.68	6.69	7.195	7.604	9.343	71	10
3.53	4.94	7.06	7.596	8.028	9.864	69	10
3.66	5.12	7.32	7.868	8.315	10.217	67	10
3.85	5.39	7.7	8.282	8.753	10.754	65	10
3.98	5.57	7.96	8.561	9.048	11.118	63	10
4.25	5.94	8.48	9.13	9.65	11.856	61	10
4.44	6.23	8.89	9.565	10.109	12.42	59	10
4.65	6.51	9.3	10.005	10.574	12.993	57	10
4.85	6.81	9.72	10.452	11.047	13.573	57	10
5	7	9.99	10.753	11.365	13.964	57	10
5.14	7.2	10.28	11.057	11.686	14.358	55	10
5.35	7.49	10.71	11.516	12.171	14.955	55	10
5.57	7.8	11.14	11.981	12.663	15.559	53	10
5.72	8	11.42	12.294	12.993	15.965	53	10

Blueprint

