


Anti-slip Mat Kargotec® Secure



Product information

Anti-slip mat for extremely heavy loads.

Kargotec® secure is the anti-slip mat for heavy loads. The combination of an exceptionally high surface load capacity (max. 500 t/m² *) and an excellent kinetic friction coefficient ($\mu = 0.80$) makes this product the first choice when it comes to securing extremely heavy loads. Highest permissible surface pressure.

Thickness: 8 mm, 10 mm.

Max. permissible surface load: (at max. 30% compression) approx. 500 t/m² at 8, 10 mm thickness.

Kinetic friction coefficient μ 0.80 at 8 and 10 mm thickness.

Elongation at break: At least 80% (DIN EN ISO 1798).

Features: Registered colour coding system (black with blue and white speckles)

Material: Recycled rubber crumbs, bonded with polyurethane

Temperature range: -30°C up to +100°C

Finish: Grain texturing

| Part Code | Dimension mm | I'd like to have more information | Delivery time |
|--------------|--------------|-----------------------------------|---------------|
| 709806476700 | 8X1250X8000 | Kargotec Secure | 10 |
| 709806497600 | 8X1250X10000 | Kargotec Secure | 10 |
| 709806454900 | 10X1250X6000 | Kargotec Secure | 10 |
| 709806627100 | 8X1500X8000 | Kargotec Secure | 10 |