



Cast-in Lifting Loop

Product information

Cast-in Lifting Loop made from endless crimped wire rope. With either plastic or steel strap (for connecting to reinforcement).

Lifting gear: The radius of the crane hook should be at least equal to the curvature of the lifting loop in order to avoid crushing of the rope.

This product complies with the requirements of the European Machinery Directive 2006/42/EC.

Material: Steel wire rope

Marking: According to standard, CE-marked

Finish: Galvanized

Standard: CEN/TR 15728 - VDI/BV-BS 6205

Safety factor: 3:1

Part Code	Load grp.	Length mm	Wire Ø mm	D mm	L mm	B mm	Weight kg	Delivery time
65041000800	0.8 t	200	6	6	200	85	0.09	2
65041001200	1.2 t	225	7	7	225	90	0.12	2
65041001600	1.6 t	235	8	8	235	100	0.15	2
65041002000	2 t	265	9	9	265	125	0.25	100
65041002500	2.5 t	285	10	10	285	145	0.34	2
65041004000	4 t	345	12	12	345	170	0.5	2
65041005200	5.2 t	390	14	14	390	195	0.99	2
65041006300	6.3 t	415	16	16	415	210	1.05	2
65041008000	8 t	460	18	18	460	225	1.49	2
65041010000	10 t	510	20	20	510	225	2.06	2
65041012500	12.5 t	570	22	22	570	295	3.31	100
65041016000	16 t	640	26	26	640	320	4.5	2
65041020000	20 t	715	28	28	715	355	5.5	2
65041025000	25 t	800	30	30	800	400	8.2	100

Blueprint

