



## Lifting Socket flat steel Anchor

### Product information

Lifting socket with welded end plate. Owing to its small depth, this socket is particularly suitable for casting into slab-type elements perpendicular to the plane of the slab.

This product complies with the requirements of the European Machinery Directive 2006/42/EC.

**Material:** Lifting sockets made from steel tube for precision applications to DIN EN 10305 (grade E 355+N)

**Marking:** According to standard, CE-marked

**Finish:** Galvanized

**Standard:** CEN/TR 15728 - VDI/BV-BS 6205

**Safety factor:** 3:1

Part Code	Thread mm	Load grp. t	Lenght mm	Finish	D mm	h mm	b mm	a mm	t mm	c mm	e mm	M mm	Weight kg	Delivery time
650575NK3510ZN	M10	0.4t	30	WZP	15	30	35	25	4	2.5	26	M10	0.04	100
650575NK3512VA	M12	0.5t	30	Stainless	15	30	35	25	4	2.5	26	M12	0.065	100
650575NK3512ZN	M12	0.5t	30	WZP	15	30	35	25	4	2.5	26	M12	0.065	100
650575NK3516VA	M16	1.2t	35	Stainless	21	35	50	35	4	3.5	31	M16	0.1	100
650575NK3516ZN	M16	1.2t	35	WZP	21	35	50	35	4	3.5	31	M16	0.1	2
650575NK3520VA	M20	2t	47	Stainless	27.2	47	60	60	5	4.5	42	M20	0.25	2
650575NK3520ZN	M20	2t	47	WZP	27.2	47	60	60	5	4.5	42	M20	0.25	2
650575NK3524VA	M24	2.5t	54	Stainless	31	54	80	60	5	4.5	49	M24	0.33	2
650575NK3524ZN	M24	2.5t	54	WZP	31	54	80	60	5	4.5	49	M24	0.33	2
650575NK3530VA	M30	4t	72	Stainless	39.5	72	100	80	6	6	66	M30	0.71	2
650575NK3530ZN	M30	4t	72	WZP	39.5	72	100	80	6	6	66	M30	0.753	2

# Blueprint

