



Lifting Socket with Bolt, without End Plate

Product information

Threaded socket with hexagon-head bolt. Owing to its small depth, this socket is particularly suitable for casting into slab-type elements perpendicular to the plane of the slab.

This product complies with the requirements of the European Machinery Directive 2006/42/EC.

Material: Stainless steel according to approval Z-30.3-6 from 22 April 2014, Grades 1.4401, 1.4404 and 1.4571. Mild steel hexagon-head bolt, Grade 8.8.

Marking: According to standard, CE-marked

Standard: CEN/TR 15728 - VDI/BV-BS 6205

Safety factor: 3:1

Part Code	Bolt mm	dxL mm	g mm	Weight kg/100pc	Delivery time
6501K38291210VA	M 12x70	M 12x100	23	9	100
6501K38291607BK	M 16x35	M 16x75	29	14	2
6501K38291215VA	M 12x120	M 12x150	23	15	100
6501K38291614BK	M 16x100	M 16x140	29	24	100
6501K38291614VA	M 16x100	M 16x140	29	24	2
6501K38292018BK	M 20x130	M 20x180	35	46	2
6501K38292018VA	M 20x130	M 20x180	35	46	100
6501K38292420BK	M 24x140	M 24x200	45	78	100
6501K38293630BK	M 36x200	M 36x300	74	270	100

Blueprint

