



Lifting Socket with Bolt, without End Plate

Product information

Threaded socket with hexagon-head bolt. Owing to its small depth, this socket is particularly suitable for casting into slab-type elements perpendicular to the plane of the slab.

This product complies with the requirements of the European Machinery Directive 2006/42/EC.

Material: Stainless steel according to approval Z-30.3-6 from 22 April 2014, Grades 1.4401, 1.4404 and 1.4571. Mild steel hexagon-head bolt, Grade 8.8.

Marking: According to standard, CE-marked

Standard: CEN/TR 15728 - VDI/BV-BS 6205

Safety factor: 3:1

Part Code	Thread mm	Lenght mm	d mm	L mm	g mm	Weight kg	Delivery time
650580K38291210BK	M12	100	M12	100	23	0.09	2
650580K38291607BK	M16	75	M16	75	29	0.14	2
650580K38291215BK	M12	150	M12	150	23	0.15	2
650580K38291614BK	M16	140	M16	140	29	0.24	100
650580K38291622BK	M16	220	M16	220	29	0.38	100
650580K38292015BK	M20	150	M20	150	35	0.41	2
650580K38292018BK	M20	180	M20	180	35	0.46	2
650580K38292420BK	M24	200	M24	200	45	0.78	100
650580K38292432BK	M24	320	M24	320	45	1.15	100
650580K38293024BK	M30	240	M30	240	60	1.56	100
650580K38293630BK	M36	300	M36	300	74	2.7	100

Blueprint

