



Lifting Socket with short-wavy Tail Bar

Product information

Lifting socket with short wavy-tail bar. The socket is anchored with a reinforcing bar. Owing to the relatively short anchorage length, these sockets are particularly for casting into wall-type elements perpendicular to the plane of the wall.

This product complies with the requirements of the European Machinery Directive 2006/42/EC.

Material: Lifting sockets made from steel tube for precision applications to DIN EN 10305 (grade E 355+N). Rebar steel Armeringsstål B500B acc. to DIN 488.

Marking: According to standard, CE-marked

Finish: Galvanized

Standard: CEN/TR 15728 - VDI/BV-BS 6205

Safety factor: 3:1

Part Code	Thread mm	Length mm	d mm	L mm	g mm	ds mm	Weight kg/100pc	Delivery time
650545K3112KM	M12	150	M12	150	25	8	0.085	100
650545K3116KM	M16	230	M16	230	27	12	0.268	100
650545K3120KM	M20	260	M20	260	34	14	0.45	100
650545K3124KM	M24	300	M24	300	43	16	0.668	100
650545K3130KM	M30	420	M30	420	56	20	1.426	100
650545K3136KM	M36	460	M36	460	69	25	2.533	100
650545K3152KM	M52	550	M52	550	100	32	5.16	100

Blueprint

