



Lifting Loop

Product information

Lifting Loop is a lifting device used for mounting on transport anchors. It is easily attached to a crane hook or other lifting equipment through the wire. The wire strap is made of wire with a threaded section at the end that is designed to fit into a transport anchor. It can be used for lifting with an angle of up to 45°. It is important to research the requirements for the maximum angle of the specific anchor to ensure safe and efficient lifting.

Areas of application: Transport anchor with internal threads.

Advantages: The wire rope stop provides an efficient way to attach lifting equipment to transport anchor. Reducing the risk of accidental disconnection.

Load group: 0.5t -4t.

Technical information: CE marking according to MD 2006/42 EF.

Marking: CE-marked, Thread size, batch code, load group

Finish: Electro-galvanized - Corrosion class C3 - ISO 12944-2.

Note: The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contact [CERTEX Danmark A/S – Starcon](#) to get information about the applicable delivery time.

Part code	Thread mm	Length mm	d mm	L mm	g mm	s mm	Weight kg	Delivery time
650424K4212MA	M12	130	M12	130	22	6	0.06	2
650424K4214MA	M14	150	M14	150	25	7	0.1	10
650424K4216MA	M16	170	M16	170	27	8	0.13	2
650424K4224MA	M24	260	M24	260	43	12	0.43	2
650424K4230MA	M30	340	M30	340	56	16	1.05	2
650424K4236MA	M36	380	M36	380	68	18	1.52	10
650424K4242MA	M42	420	M42	420	80	20	2.18	10

Blueprint

