



## Wall Mounted Jib Crane OB

### Product information

Wall mounted jib cranes comprise an arm and a pair of brackets that can be bolted or welded to an existing wall or building column/stanchion/pillar. A structural engineer must test the support structure to ensure it is strong enough to sustain the weight of the jib crane when loaded.

The arm is located between the clamping brackets and fixed using a pivot pin. The arm rotates around the support column and enables lifting within a predetermined arc.

#### Features:

- Capacity up to 1000 kg
- Outreach up to 6 m
- Electrical festoon supply: runs inside the arm track

**Material:** Stainless steel 304/316

**Finish:** Zinc plated/powder coating



**Contact our crane specialists**

Send us a message and we will get back to you as soon as possible.

[hubspot]

WLL ton	Length m	Thread	B mm	R mm	B2 mm	h1 mm	W1	W2	Delivery time
0.08	3	M20	500	3,000	720	65	500	380	10
0.08	4	M20	600	4,000	820	65	500	380	10
0.08	5	M20	900	5,000	1,120	65	500	380	10
0.08	6	M20	900	6,000	1,120	77	500	380	10
0.125	3	M20	500	3,000	720	77	500	380	10
0.125	4	M20	600	4,000	820	77	500	380	10
0.125	5	M20	900	5,000	1,120	77	500	380	10
0.125	6	M20	1,000	6,000	1,220	77	500	380	10
0.25	3	M20	600	3,000	820	77	500	380	10
0.25	4	M20	800	4,000	1,020	77	500	380	10
0.25	5	M20	900	5,000	1,120	94	500	380	10
0.25	6	M20	1,000	6,000	1,220	94	500	380	10
0.5	3	M20	800	3,000	1,020	94	500	380	10
0.5	4	M20	900	4,000	1,120	94	500	380	10
0.5	5	M20	1,000	5,000	1,220	123	500	380	10
0.5	6	M20	1,100	6,000	1,320	123	500	380	10
1	3	M20	900	3,000	1,120	123	500	380	10
1	4	M20	1,000	4,000	1,220	123	500	380	10

# Blueprint

