

## Open Wedge Socket OWS P with Pin



### Product information

Intended for attaching of wire rope where switching often occur, e.g. blocks of mobilecranes, or to be able to adjust the length of the wire rope. See recommended assembly to get correct results.

The wedge socket is delivered complete with wedge, pin and cotterpin.

2 surface finishes available:

- Model OWS P : blue painted.
- Model OWS PGAL : Hot dipped galvanized.

Model OWS 0.25 and OWS 0.5 only standard available in hot dipped galvanized.

**Material:** Quenched and tempered cast steel

**Marking:** Size, wire rope diameter and batch or serial number.

**Temperature range:** -40°C to +100°C - Use at higher temperatures possible with reduction of WLL.

**Finish:** Blue painting or hot dipped galvanized

**Note:** The efficiency of a 6 and 8 strand wire rope/wedge socket connection is 80% of the minimum breaking load of the wire but limited to the minimum breaking load of the socket (MBL).

Part Code	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	ØP mm	T mm	TL mm	TB mm	W mm	Weight kg	Delivery time
121501000202	9-10	12	Galvanized	145	23	46	21	11	168	63	21	1.7	10
121501300202	11-13	20	Galvanized	157	29	57	25	12	185	67	25	2.1	10
121501600202	14-16	25	Galvanized	190	35	70	30	15	225	85	31	4	10
121501900202	18-19	40	Galvanized	210	40	80	35	16	250	95	38	7	10
121502200202	20-22	55	Galvanized	252	48	95	41	18	300	110	44	10	10
121502600202	23-26	75	Galvanized	298	55	110	51	22	353	128	51	15	10
121502900202	27-29	90	Galvanized	322	65	130	57	25	387	142	57	21	10
121503200202	30-32	110	Galvanized	350	73	146	63	28	423	155	63	31	10
121503600202	34-36	125	Galvanized	400	74	148	64	28	474	160	70	37	10
121503900202	37-39	150	Galvanized	450	80	142	70	30	530	177	77	51	10

# Blueprint

