



Wire Rope Sheave, type SR

Product information

Wire rope sheave in maintenance-free design for manual and power operation. With plain bushing. Grooved profile turned to DIN 15061.

Material: S355J2.

Finish: Galvanized.

Note: Also available with ball-bearing, for higher load.

| Part Code | Rope Ø range mm | Bearing | Type | Max. load ton | D1 mm | D2 mm | R mm | d1 mm | B mm | b mm | Weight kg | Delivery time |
|--------------|-----------------|----------------|----------|---------------|-------|-------|------|-------|------|------|-----------|---------------|
| 140100600120 | 2-6 | - | SR 050 G | 0.1 | 50 | 38 | 3,2 | 10 | 16 | 12 | 0.1 | 2 |
| 140100800120 | 3-8 | - | SR 075 G | 0.2 | 75 | 59 | 4,2 | 12 | 20 | 18 | 0.3 | 2 |
| 140100900120 | 4-9 | - | SR 100 G | 0.3 | 100 | 80 | 4,8 | 16 | 25 | 21 | 0.6 | 2 |
| 140101000121 | 6-10 | Bronze bearing | SR 125 G | 0.5 | 125 | 103 | 5,3 | 16 | 25 | 21 | 0.9 | 10 |
| 140101000125 | 6-10 | Bronze bearing | SR 200 G | 1.5 | 200 | 166 | 5,3 | 30 | 38 | 32 | 4.5 | 2 |
| 140101200121 | 8-12 | Bronze bearing | SR 150 G | 0.75 | 150 | 126 | 6,5 | 20 | 25 | 22 | 1.4 | 2 |
| 140101200125 | 10-12 | Bronze bearing | SR 250 G | 2 | 250 | 213 | 6,5 | 40 | 41 | 36 | 7.9 | 10 |
| 140101600120 | 12-16 | - | SR 300 G | 4 | 300 | 257 | 8,5 | 50 | 62 | 40 | 12.8 | 10 |

Blueprint

