

Wire Pulley Sheave, type BR



Product information

Pulley sheaves for rope deflection with plain bearing, with honed steel axle. Grooved profile turned to DIN 15061.

Material: Sheave: S355J2. Mounting plate: gray cast iron GG20.

Finish: Wire rope sheave: galvanized, mounting plate: painted.

Note: Also available with ball-bearing, for higher load.

| Part Code | Rope Ø range mm | Type | Max load ton | D1 mm | D2 mm | R mm | A x B | C mm | E x F | H mm | øL | Weight kg | Delivery time |
|--------------|-----------------|----------|--------------|-------|-------|------|----------|------|---------|------|----|-----------|---------------|
| 140100600130 | 2-6 | BR 050 G | 0.3 | 50 | 38 | 3,2 | 67 x 67 | 7 | 50 X 50 | 35 | 7 | 0.6 | 10 |
| 140100800130 | 3-8 | BR 075 G | 0.6 | 75 | 59 | 4,2 | 75 x 75 | 10 | 60 X 60 | 50 | 9 | 1.4 | 10 |
| 140100900130 | 4-9 | BR 100 G | 0.9 | 100 | 80 | 4,8 | 90 x 90 | 10 | 70 X 70 | 65 | 12 | 2.5 | 10 |
| 140101000130 | 6-10 | BR 125 G | 1.1 | 125 | 103 | 5,3 | 92 x 92 | 10 | 70 X 70 | 75 | 12 | 3.2 | 10 |
| 140101200130 | 8-12 | BR 150 G | 1.25 | 150 | 126 | 6,5 | 12 x 100 | 12 | 75 X 90 | 90 | 14 | 4.8 | 2 |

Blueprint

