

Wire Pulley Block, type SB



Product information

Pulley sheaves for rope deflection with plain bearing, with honed steel axle. Grooved profile turned to DIN 15061.

Material: S355J2.

Finish: Galvanized.

Note: Also available with ball-bearing, for higher load.

| Part Code | Rope Ø range mm | Type | Max load ton | D1 mm | D2 mm | R mm | A/B | C mm | E / (F) | H1 mm | H2 mm | ØL | Weight kg | Delivery time |
|--------------|-----------------|----------|--------------|-------|-------|------|-----------|------|---------|-------|-------|----|-----------|---------------|
| 140100600140 | 2-6 | SB 050 G | 0.05 | 50 | 38 | 3,2 | 115 / 95 | 7 | 30 / - | 21,5 | 35 | 9 | 0.5 | 10 |
| 140100800140 | 3-8 | SB 075 B | 0.1 | 75 | 59 | 4,2 | 140 / 120 | 10 | 30 / - | 25 | 41 | 11 | 0.9 | 10 |
| 140100900140 | 4-9 | SB 100 G | 0.15 | 100 | 80 | 4,8 | 175 / 145 | 10 | 40 / - | 26,5 | 45 | 11 | 1.3 | 10 |
| 140101000140 | 6-10 | SB 125 G | 0.25 | 125 | 103 | 5,3 | 200 / 170 | 10 | 60 / 30 | 28,5 | 48 | 11 | 2.5 | 10 |
| 140101200140 | 8-12 | SB 150 G | 0.5 | 150 | 126 | 6,5 | 230 / 200 | 12 | 60 / 30 | 28,5 | 48 | 11 | 3.3 | 10 |

Blueprint

