

## Wedge Socket for Lifts

### Product information

Symmetrical Wedge Socket for stranded steel wire ropes according to EN 12385-5 for lifts.

**Marking:** According to standard

**Temperature range:** -20°C up to +100°C

**Finish:** Galvanized

**Standard:** EN 13411-7

*DIN 15315 replaced by EN 13411-7*

**Warning:** Tensile strength should not exceed 1770 N/mm<sup>2</sup>



| Part Code    | Rope Ø range<br>mm | Finish     | B1<br>mm | B2<br>mm | B3<br>mm | C<br>mm | D<br>mm | E<br>mm | H1<br>mm | H2<br>mm | H3<br>mm | R<br>mm | S<br>mm | Weight<br>kg | Delivery time |
|--------------|--------------------|------------|----------|----------|----------|---------|---------|---------|----------|----------|----------|---------|---------|--------------|---------------|
| 121500800072 | 6-8                | Galvanized | 12       | 14       | 11       | 37      | 12      | 20      | 150      | 75       | 92       | 12,5    | 4       | 0.57         | 10            |
| 121501100072 | 9-11               | Galvanized | 15       | 17       | 14       | 48      | 16      | 26      | 190      | 95       | 117      | 16      | 6       | 1.05         | 10            |
| 121501400072 | 12-14              | Galvanized | 20       | 22       | 18       | 58      | 18      | 32      | 230      | 115      | 141      | 19      | 8       | 1.89         | 10            |
| 121501700072 | 15-17              | Galvanized | 23       | 25       | 21       | 70      | 22      | 36      | 260      | 130      | 162      | 23      | 10      | 3.26         | 10            |

# Blueprint

