

## **Anchor Starcon Load Group 20 t**

## **Product information**

The Starcon spherical head anchor load group 20 t is a steel component made for concrete casting. The foot of the anchor is constructed especially for strong concrete anchorage.

The cylindrical head of the Starcon spherical anchor is attached to a Stardon Lifting eye, standard coupling lifting eye for lifting.

Engelsk: The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

Finish: Untreated, hot dip galvanized or stainless

**Note:** The delivery time for the individual products is estimated. If the desired quantity is not in stock, please contact CERTEX Danmark A/S <u>Starcon</u> for information on the applicable delivery time.

Part Code	Load grp.	Length mm	Finish	D mm	D1 mm	D2 mm	L mm	Weight kg	Delivery time
65011020002501	20.0t	250	Untreated	39	70	98	250	3.3	2
65011020002502	20.0t	250	HDG	39	70	98	250	3.3	100
65011020003401	20.0t	340	Untreated	39	70	98	340	4.38	100
65011020003402	20.0t	340	HDG	39	70	98	340	4.38	2
65011020005001	20.0t	500	Untreated	39	70	98	500	5.87	2
65011020005002	20.0t	500	HDG	39	70	98	500	5.87	100
65011020010001	20.0t	1,000	Untreated	39	70	98	1,000	11.75	2
65011020010002	20.0t	1,000	HDG	39	70	98	1,000	11.75	100

## Blueprint

