


## Anchor Starcon Load Group 15 t



### Product information

The Starcon spherical head anchor load group 15 t is a steel component made for concrete casting. The foot of the anchor is constructed especially for strong concrete anchorage.

The cylindrical head of the Starcon spherical anchor is attached to a Starcon Lifting eye, standard coupling lifting eye for lifting.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

**Marking:** CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

**Finish:** Untreated, hot dip galvanized or stainless

**Note:** The delivery time for the individual products is estimated. If the desired quantity is not in stock, please contact CERTEX Danmark A/S [Starcon](#) for information on the applicable delivery time.

Part Code	Load grp.	Length mm	Finish	D mm	D1 mm	D2 mm	L mm	Weight kg	Delivery time
65011015001651	15.0t	165	Untreated	34	69	85	165	1.97	2
65011015001652	15.0t	165	HDG	34	69	85	165	1.97	100
65011015002001	15.0t	200	Untreated	34	69	85	200	2.21	2
65011015002002	15.0t	200	HDG	34	69	85	200	2.21	2
65011015003001	15.0t	300	Untreated	34	69	85	300	2.91	2
65011015003002	15.0t	300	HDG	34	69	85	300	2.91	2
65011015004001	15.0t	400	Untreated	34	69	85	400	3.59	100
65011015004002	15.0t	400	HDG	34	69	85	400	3.59	100

## Blueprint

