



Double Headed Anchor Starcon Load Group 1,3 t

Product information

The Starcon double headed anchor load group 1,3 t is a steel component made for concrete casting. The foot of the anchor is constructed especially for strong concrete anchorage. The cylindrical head of the Starcon double headed anchor is attached to a Starcon lifting eye for lifting.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

Finish: Untreated, or hot dip galvanized

Note: The delivery time for the individual products is estimated. If the desired quantity is unavailable, please contact CERTEX Danmark A/S [Starcon](#) for information on the applicable delivery time.

Part Code	Load grp.	Length mm	Finish	L mm	D mm	D1 mm	D2 mm	Weight kg	Delivery time
65011101300402	1.3t	40	HDG	40	10	19	25	0.06	100
65011101300452	1.3t	45	HDG	45	10	19	25	0.06	100
65011101300651	1.3t	65	Untreated	65	10	19	25	0.07	100
65011101300652	1.3t	65	HDG	65	10	19	25	0.07	100
65011101300852	1.3t	85	HDG	85	10	19	25	0.09	2
65011101301201	1.3t	120	Untreated	120	10	19	25	0.11	100
65011101301202	1.3t	120	HDG	120	10	19	25	0.11	100

Blueprint

