



Double Headed Anchor Starcon Load Group 1,3 t

Product information

The Starcon double headed anchor load group 1,3 t is a steel component made for concrete casting. The foot of the anchor is constructed especially for strong concrete anchorage. The cylindrical head of the Starcon double headed anchor is attached to a Starcon lifting eye for lifting.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

Finish: Untreated, or hot dip galvanized

Note: The delivery time for the individual products is estimated. If the desired quantity is unavailable, please contact CERTEX Danmark A/S [Starcon](#) for information on the applicable delivery time.

| Part Code | Load grp. | Length mm | Finish | L mm | D mm | D1 mm | D2 mm | Weight kg | Delivery time |
|----------------|-----------|-----------|-----------|------|------|-------|-------|-----------|---------------|
| 65011101300402 | 1.3t | 40 | HDG | 40 | 10 | 19 | 25 | 0.06 | 100 |
| 65011101300452 | 1.3t | 45 | HDG | 45 | 10 | 19 | 25 | 0.06 | 100 |
| 65011101300651 | 1.3t | 65 | Untreated | 65 | 10 | 19 | 25 | 0.07 | 100 |
| 65011101300652 | 1.3t | 65 | HDG | 65 | 10 | 19 | 25 | 0.07 | 100 |
| 65011101300852 | 1.3t | 85 | HDG | 85 | 10 | 19 | 25 | 0.09 | 2 |
| 65011101301201 | 1.3t | 120 | Untreated | 120 | 10 | 19 | 25 | 0.11 | 100 |
| 65011101301202 | 1.3t | 120 | HDG | 120 | 10 | 19 | 25 | 0.11 | 100 |

Blueprint

