



## Double Headed Anchor Starcon Load Group 2,5 t

### Product information

The Starcon double headed anchor is a steel component made for concrete casting.  
The foot of the anchor is constructed especially for strong concrete anchorage.  
The cylindrical head of the Starcon double headed anchor is attached to a Starcon lifting eye for lifting.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

**Marking:** CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

**Finish:** Untreated, or hot dip galvanized

**Note:** The delivery time for the individual products is estimated. If the desired quantity is unavailable, please contact CERTEX Danmark A/S [Starcon](#) for information on the applicable delivery time.

Part Code	Load grp.	Length mm	Finish	L mm	D mm	D1 mm	D2 mm	Weight kg	Delivery time
65011102500452	2.5t	45	HDG	45	14	26	35	0.12	100
65011102500552	2.5t	55	HDG	55	14	26	35	0.13	100
65011102500682	2.5t	68	HDG	68	14	26	35	0.15	100
65011102500851	2.5t	85	Untreated	85	14	26	35	0.18	100
65011102500852	2.5t	85	HDG	85	14	26	35	0.18	2
65011102501201	2.5t	120	Untreated	120	14	26	35	0.22	100
65011102501202	2.5t	120	HDG	120	14	26	35	0.22	100
65011102501701	2.5t	170	Untreated	170	14	26	35	0.27	100
65011102501702	2.5t	170	HDG	170	14	26	35	0.27	100

## Blueprint

