



Double Headed Anchor Starcon Load Group 5,0 t

Product information

The Starcon double headed anchor is a steel component made for concrete casting. The foot of the anchor is constructed especially for strong concrete anchorage. The cylindrical head of the Starcon double headed anchor is attached to a Starcon lifting eye for lifting.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

Finish: Untreated, or hot dip galvanized

Note: The delivery time for the individual products is estimated. If the desired quantity is unavailable, please contact CERTEX Danmark A/S [Starcon](#) for information on the applicable delivery time.

Part Code	Load grp.	Length mm	Finish	L mm	D mm	D1 mm	D2 mm	Weight kg	Delivery time
65011105000752	5.0t	75	HDG	75	20	36	50	0.35	100
65011105000952	5.0t	95	HDG	95	20	36	50	0.4	100
65011105001102	5.0t	110	HDG	110	20	36	50	0.44	100
65011105001101	5.0t	110	Untreated	110	20	36	50	0.44	100
65011105001202	5.0t	120	HDG	120	20	36	50	0.46	100
65011005001401	5.0t	140	Untreated	140	20	36	50	0.5	100
65011105002401	5.0t	240	Untreated	240	20	36	50	0.78	100
65011105002402	5.0t	240	HDG	240	20	36	50	0.78	100

Blueprint

