



Swivel Eye / Jaw Crosby S4

Product information

Design: Swivel with eye and jaw equipped with tapered roller thrust bearing.

Features:

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided.
- All jaws complete with bolts, nuts and cotter pins.
- Other types and capacities up to 1250 t available on demand.

Marking: CE-marked

Note: Always check before use if your steel wire rope is suitable for use with a swivel.

Warning: Not to be used on demolition- (wrecking-) balls!

Safety factor: 5:1

| Part Code | Rope Ø range mm | WLL ton | Swivel No | C mm | G mm | H mm | J mm | K mm | N mm | O mm | Q mm | R mm | S mm | T mm | Weight kg | Delivery time |
|--------------|--------------------|------------|-----------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|--------------|---------------|
| 422500300110 | 13 | 3 | 3-S-4 | 237 | 70 | 19.1 | 22.4 | 41.1 | 33.3 | 25.4 | 19.1 | 26.2 | 28.4 | 31.8 | 4.08 | 10 |
| 422500500110 | 16 | 5 | 5-S-4 | 256 | 76 | 22.4 | 25.4 | 57 | 41.1 | 28.4 | 25.4 | 32.5 | 31.8 | 31.8 | 5.6 | 10 |
| 422502500110 | | 25 | 25-S-4 | 546 | 152 | 51 | 51 | 117 | 93.5 | 60.5 | 57 | 58.5 | 98.5 | 60.5 | 61 | 10 |

Blueprint

