



## Swivel Eye / Jaw Crosby S4

### Product information

**Design:** Swivel with eye and jaw equipped with tapered roller thrust bearing.

**Features:**

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided.
- All jaws complete with bolts, nuts and cotter pins.
- Other types and capacities up to 1250 t available on demand.

**Marking:** CE-marked

**Note:** Always check before use if your steel wire rope is suitable for use with a swivel.

**Warning:** Not to be used on demolition- (wrecking-) balls!

**Safety factor:** 5:1

Part Code	Rope Ø range mm	WLL ton	Swivel No	C mm	G mm	H mm	J mm	K mm	N mm	O mm	Q mm	R mm	S mm	T mm	Weight kg	Delivery time
422500300110	13	3	3-S-4	237	70	19.1	22.4	41.1	33.3	25.4	19.1	26.2	28.4	31.8	4.08	10
422500500110	16	5	5-S-4	256	76	22.4	25.4	57	41.1	28.4	25.4	32.5	31.8	31.8	5.6	10
422502500110		25	25-S-4	546	152	51	51	117	93.5	60.5	57	58.5	98.5	60.5	61	10

Blueprint

