

Starcon Eye Anchor



Product information

The Starcon eye anchor is a steel component made for concrete casting. The foot of the anchor is constructed especially for strong concrete anchorage.

The cylindrical head of the Starcon eye anchor is attached to a Starcon lifting eye for lifting.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

Finish: Untreated, or hot dip galvanized

Note: The delivery time for the individual products is estimated. If the desired quantity is unavailable, please contact CERTEX Danmark A/S [Starcon](#) for information on the applicable delivery time.

Part Code	Load grp. t	Length mm	Finish	D mm	D1 mm	H mm	L mm	Ø mm	Weight kg	Delivery time
65011301300651	1.3	65	Untreated	10	19	22	65	10	0.06	100
65011301300652	1.3	65	HDG	10	19	22	65	10	0.06	2
65011002500451	2.5	90	Untreated	14	26	32	90	14	0.17	100
65011002500452	2.5	90	HDG	14	26	32	90	14	0.17	100
65011305001201	5	120	Untreated	20	36	43	120	20	0.43	2
65011305001202	5	120	HDG	20	36	43	120	20	0.73	100
65011310001151	10	115	Untreated	28	46	57	115	25	0.77	2
65011310001801	10	180	Untreated	28	46	57	180	25	1.16	2
65011310001802	10	180	HDG	28	46	57	180	25	1.16	100
65011320002501	20	250	Untreated	39	70	82	250	38	3.17	2
65011320002502	20	250	HDG	39	70	82	250	38	3.17	2

Blueprint

